Power PRO series
X400

14 MP | 15X Zoom | 2.7" LCD

Available Colors:

Images are simulated.

More power, More full

Shoot like a Pro with the X400 from GE. The X400 is a unique design packed with all the features and latest technology you've come to expect from GE. Wide angle lens, super long zoom and more than 30 camera settings are just the start. What are you waiting for? Power and performance has never been more affordable.

imagination at work

Camera Features

X400

15x optical zoom
Powerful optical zoom moves you closer to the subject for tight, clear shots.

3200 ISO
Improves pictures in low lighting condition for optimal exposure.

optical image stabilization
Automatically adjusts unintentional camera movements giving you clear, crisp pictures every time.

AA battery
Convenient, easy and no hassle AA batteries keep you on the go.

auto scene
Automatically selects and sets the correct scene type for the sharpest, most vibrant pictures possible.

pancapture
Wide-view photos are produced by panning the camera across to create a seamless panoramic picture.

face auto exposure
Automatically enhances facial features detected by the camera for true subject highlighting.

high dynamic range
In-camera feature adjusts exposure for more detail in light and dark scenes.

SPECIFICATIONS*	X400
Number Of Active Pixels	14.14 Megapixels
Image Sensor	14.48 Megapixels [1/2.33" Charge Coupled Device (CCD)]
Lens Focal Length F =	4.9 mm (Wide) — 73.5 mm (Tele)
[35mm film equivalent]	[27 mm (Wide) — 405 mm (Tele)
F number	f / 3.0 (Wide) — f / 5.2 (Tele)
Lens Construction	14 elements in 11 groups
Optical Zoom	15X
Focusing Range	Macro: (Wide) 1.9 in. ~ ∞ / 5 cm ~ ∞ Normal: (Wide) 23.6 in. ~ ∞ / 60 cm ~ ∞, (Tele) 47.2 in. ~ ∞ / 120 cm ~ ∞
Anti-Handshake	Optical Image Stabilization (CCD-shift type)
Digital Zoom	6 x Digital Zoom (Combined Zoom: 905x)
Number of Recording Pixels	
Still Image	14MP: 4320×3240, (3:2), 12MP: 4320x2880, 8MP: 3264×2448, 5MP: 2592×1944, 3MP: 2048×1536, (16:9) 2MP: 1920×1080, 0.3MP: 640×480
Movie	VGA, QVGA
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.2 (JPEG)
Movie	Movie Format: MOV(Motion JPEG), Audio: G.711[Monaural]
Shooting Modes	Auto, ASCN, P, S, A, M, Portrait , Panorama, Movie, Scene (Sport, Children, Indoor, Leaf, Snow, Beach, Text, Party, ID, Fisheye, Panning shot, Photo frame, Sketch, Sunset, Fireworks, Glass, Museum, Landscape, Night Landscape, Night Portrait)
Detection Features	Face, Smile, Blink
Red-eye Removal	Yes
High Dynamic Range	Yes (Post-Processing)
LCD Display	2.7 inch (230,400 pixels)
Panorama Capture Still Image	Yes (Horizontal)
View Angle	0° ~ 170°
ISO Sensitivity	Auto, ISO 80 / 100 / 200 / 400 / 800 / 1600 (4M) / 3200 (4M)
AF Method	Single AF, Multi-AF (TTL 13-point), Face-Detection + Face AE, AF Assist Light (On / Off)
Exposure Metering Method	Artificial Intelligence AE (Ai AE), Center-weighted Average, Spot (Fixed to center of frame)
Exposure Control Method	Program AE (AE-lock available), Aperture prior AE, Shutter Prior AE
Exposure Compensation	± 2 EV in 1/3 Step increments
Shutter Speed	4 ~ 1/2000 seconds (Manual: 30 seconds)
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9 / 16 thumbnails), Slide Show, Movie, Date, Zoom (Approx. 2x~ 8x), Audio, Histogram Display
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, CWF, Incandescent, Manual
Flash	Pop-up
Flash Modes	Auto, Red-Eye Reduction, Forced Flash, No Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 11.8 in. ~ 177.1 in. / Approx. 0.3 m ~ 4.5 m (ISO 800) (Tele) Approx. 19.6 in. ~ 157.4 in. / Approx. 0.5 m ~ 4.0 m (ISO 800)
Recording Media	Internal memory: Approx. 13MB SD Card / SDHC Card (Up to 16 GB support)
Other Features	PictBridge, ExifPrint Support, Multi-language Support (26 languages)
Jacks	USB 2.0 / AV-OUT
Power	4xAA Alkaline Battery, 4xAA NiMH Battery [Not Included]
Shooting Capability (Battery Performance)	Approx. 300 shots for AA Alkaline Batteries (based on CIPA Standards) Approx. 500 shots for AA NiMH Batteries (based on CIPA Standards) (NiMH Battery: 2500mAh / pcs) [Not Included]
Operation Environment	Temperature: 32° ~ 104° F / 0° ~ 40°C, Humidity: 0 ~ 90%
Dimensions (W x H x D)	4.06 in x 2.92 in x 2.68in /103 mm x 74 mm x 68 mm
Mass	Approx. 12 oz / 350g (Body Only)
Supplied Accessories	4xAA Alkaline Battery, USB Cable, Shoulder Strap, CD-ROM, Lens Cover, Quick Start Guide, Feature Guide, Warranty Card

*Design and specifications are subject to change without notice.
For complete specifications and detailed product information, please visit www.ge.com/digitalcameras.